Construction Scaffold & Debris Nets



Where there's construction, there's debris –falling or flying objects that can seriously injure people and severely damage property if not for the safeguard of protective netting.

Construction netting consisting of scaffold wind/sun block and vertical debris nets can wrap a building in safety, protecting workers, pedestrians, and nearby structures from harm of falling material.

InCord scaffold and debris netting, a standard in the industry, is available in small mesh size for wind and sun bloc to 1/4 inch heavy strength mesh. Debris netting may be used in a stacked configuration or used as a liner in combination with structural netting such as personnel safety nets.

Our scaffold and debris nets are ultra-durable, reusable, and can be moved from floor to floor. Our scaffold netting complies with OSHA regulations and meets CPAI-84, Section 6, Tent Walls and Tops.

An Authorized InCord Distributor

Full Circle Group



Sold by





We can provide you with in-stock netting or custom netting.



Scaffold and Debris Nets improve productivity and reduces downtime from accidents and clean up.


OSHA

Specifications and Sizes

Model	Material	Color	Thickness inch	Weft holes/inch	Warp holes/inch	Opacity	Ball Burst ASTM D3786	Weight oz/sq yd	FR Rating	Tarp Sizes	Roll Goods
RPY13AN	knit polyester	white green	0.0475	9.75	11.75	85%	500 lbf/in ²	13.7	no¹	custom	8' 4" x 150'
WS85	knit polyester	sand	0.0325	9.75	11.75	85%	209 lbf/in ²	5.3	no ¹	custom	6' x 150'
WS70 BK HDPE	high density polyethylene	black	0.0450	5.00	7.50	70%	312 lbf/in ²	5.1	no	custom	max. width 16 ft (5 m) max. length 164 ft (50 m)
WS70 WH WS70 GN HDPE	high density polyethylene	white green	0.0350	5.00	7.50	70%	>100 lbf/in ²	4.4	no	custom	8' x 150' wh, gn 8.5' x 150' wh 10' x 300' gn
WS70 PP	polypropylene	black	0.0350	5.00	7.50	70%	341 lbf/in ²	6.4	no	PSN	
WS70 FR	polyethylene	black ²	0.0350	5.00	7.50	70%	160 lbf/in ²	4.4	NFPA-701	custom	8' x 150' 8' 6" x 150'
Model	Material	Color	Thickness inch	Mesh Size		Breaking Strength ASTM D5034 Warp (1 inch grab) Weft		Weight oz/sq yd	FR Rating	Tarp Sizes	Roll Goods
DNR18	PVC coated polyester	orange	0.0185	1/8 x 3/16 inch		179 lbf/in ²	94 lbf/in ²	5.90	NFPA-701	NA	4' x 150' 5' 6" x 150'
DNR75	knit polyethylene	black	0.035	5/16 inch		87.7 lbf/in ²	66.4 lbf/in ²	3.40	no	NA	4' x 150' 8.5' x 150' 10' 6" x 150'
DNR75 FR	knit polyethylene	orange blue	0035	5/16 inch		87.7 lbf/in ²	66.4 lbf/in ²	3.40	NFPA-701	NA	4' x 150' 5' 6" x 150' 8.5' x 150' 10' 6" x 150'
Model	Material	Color ³	Thickness inch	Mesh Size		Breaking Strength ASTM D3787 Ball Burst		Weight oz/sq yd	FR Rating	Tarp Sizes	Roll Goods
DNR800 FR	knit polyester	white	0.043	3/8 inch		125 lbf/in ²		4.15	NFPA-701	custom	10' x 300'
DNR900 FR	knit polyester	black	0.043	3/8 inch		125 lbf/in ²		4.15	NFPA-701	custom	10' x 300'

1. NFPA-701 version available on special order 2. Available Colors: black, white, green. 3. Std. Colors: sand, merlot, green, white, gray, black – custom colors available.

Debris liners are available in roll form with selvage edge with button holes or in tarp configurations with a web border and grommets. Please note that we specialize in custom netting, call for a quotation on other sizes.



Call Full Circle Group for all your netting needs at 212-933-9071





76 Beaver St. 15th Floor New York, NY 10005 212.933.9071



InCord is an ISO 9001 registered company CAGE Code No. 1NPR7